

## 寸法表

(単位: mm)

## UFC固定フランジ寸法表

型式	寸法	フランジ寸法							タイプ	接続パイプ		ボルト		ガスケット型式 (外径×内径×厚さ)
		A	B	PCD	C	D	K	d		外径	内径	径×長さ	N	
UFC034-000FH	FT	33.8	—	27.0	7.2	1.2	18.3	4.4 (M4)	c	—	—	M4×20 (16)	6	UFC034G (21.3×16.3×2)
UFC034-006FHS	FTS	33.8	6.4	27.0	7.2	1.2	18.3	4.4 (M4)	d	6.35	4.35			
UFC034-010FH	FT	33.8	10.2	27.0	7.2	4.6	10.2	4.4 (M4)	b	10.0	8.0			
UFC034-010FHS	FTS	33.8	10.2	27.0	7.2	1.2	18.3	4.4 (M4)	d	10.0	8.0			
UFC034-018FH	FT	33.8	18.0	27.0	7.2	11.2	15.0	4.4 (M4)	e	18.0	16.0	M5×30 (20)	6	UFC054G (34.8×26.0×2)
UFC054-000FH	FT	54.0	—	43.0	10.0	3.5	26.5	6.0 (M5)	a	—	—			
UFC054-022FH	FT	54.0	22.2	43.0	10.0	5.0	22.2	6.0 (M5)	b	21.7	18.7	M6×35 (25)	6	UFC070G (48.1×36.9×2)
UFC054-025FH	FT	54.0	25.7	43.0	10.0	5.0	25.7	6.0 (M5)	b	25.4	22.4			
UFC070-000FH	FT	69.3	—	58.7	12.7	3.8	34.8	6.8 (M6)	a	—	—	M6×35 (25)	6	UFC070G (48.1×36.9×2)
UFC070-025FH	FT	69.3	25.7	58.7	12.7	5.3	25.7	6.8 (M6)	b	25.4	22.4			
UFC070-032FH	FT	69.3	31.9	58.7	12.7	5.3	31.9	6.8 (M6)	b	31.8	28.8			
UFC070-040FH	FT	69.3	38.3	58.7	12.7	5.3	38.3	6.8 (M6)	b	38.1	35.1			
UFC070-042FH	FT	69.3	42.9	58.7	12.7	10.7	39.0	6.8 (M6)	m	42.7	39.4	M8×45 (35)	8	UFC070GS (48.1×40.0×2)
UFC114-000FH	FT	113.5	—	92.2	17.5	5.0	63.8	8.5 (M8)	a	—	—			
UFC114-065FH	FT	113.5	63.8	92.2	17.5	7.0	63.8	8.5 (M8)	b	63.5	59.5	M8×50 (40)	16	UFC114G (82.4×63.7×2)
UFC152-000FH	FT	151.6	—	130.3	19.8	4.8	102.0	8.5 (M8)	a	—	—			
UFC152-100FH	FT	151.6	102.0	130.3	19.8	7.1	102.0	8.5 (M8)	b	101.6	97.6	M8×55 (45)	20	UFC152G (120.5×101.8×2)
UFC203-000FH	FT	202.4	—	181.1	22.4	9.7	152.9	8.5 (M8)	a	—	—			
UFC203-150FH	FT	202.4	152.9	181.1	22.4	12.7	152.9	8.5 (M8)	b	152.4	146.4	M8×60 (50)	24	UFC203G (171.2×152.6×2)
UFC253-000FH	FT	253.2	—	231.9	24.6	9.7	203.7	8.5 (M8)	a	—	—			
UFC253-200FH	FT	253.2	203.8	231.9	24.6	12.7	203.7	8.5 (M8)	b	203.2	197.2	M8×65 (55)	32	UFC253G (222.1×203.4×2)
UFC306-000FH	FT	306.0	—	284.0	27.0	10.0	256.0	8.5 (M8)	a	—	—			
UFC306-250FH	FT	306.0	256.0	284.0	27.0	13.0	256.0	8.5 (M8)	b	254.0	248.0	M8×65 (55)	32	UFC306G (273.0×258.0×2)

※FH、FHSは通しボルト穴型、FT、FTSはタップ穴型です。

※フランジ寸法のdおよびボルト寸法の数値はFH、FHSの寸法で( )内の数値はFT、FTSの寸法です。

## UFC回転フランジ寸法表

型式	寸法	フランジ寸法							タイプ	接続パイプ		ボルト		ガスケット型式 (外径×内径×厚さ)	
		A	B	PCD	C	D	E	K		d	外径	内径	径×長さ		N
UFC034-000RH		33.8	—	27.0	7.2	1.2	5.8	18.3	4.4	l	—	—	M4×20	6	UFC034G (21.3×16.3×2)
UFC034-006RHS		33.8	6.4	27.0	7.2	1.2	5.8	18.3	4.4	i	6.35	4.35			
UFC034-010RH		33.8	10.2	27.0	7.2	4.6	5.8	10.2	4.4	k	10.0	8.0			
UFC034-010RHS		33.8	10.2	27.0	7.2	1.2	5.8	18.3	4.4	i	10.0	8.0			
UFC034-018RH		33.8	18.0	27.0	7.2	11.2	5.8	15.0	4.4	j	18.0	16.0	M5×30	6	UFC054G (34.8×26.0×2)
UFC054-000RH		54.0	—	43.0	10.0	1.2	6.6	29.6	6.0	h	—	—			
UFC054-022RH		54.0	22.2	43.0	10.0	5.0	6.6	22.2	6.0	g	21.7	18.7	M6×35	6	UFC070G (48.1×36.9×2)
UFC054-025RH		54.0	25.7	43.0	10.0	5.0	6.6	25.7	6.0	g	25.4	22.4			
UFC070-000RH		69.3	—	58.7	12.7	2.0	7.6	41.3	6.8	h	—	—	M6×35	6	UFC070G (48.1×36.9×2)
UFC070-025RH		69.3	25.7	58.7	12.7	5.3	7.6	25.7	6.8	g	25.4	22.4			
UFC070-032RH		69.3	31.9	58.7	12.7	5.3	7.6	31.9	6.8	g	31.8	28.8			
UFC070-040RH		69.3	38.3	58.7	12.7	5.3	7.6	38.3	6.8	g	38.1	35.1			
UFC114-000RH		113.5	—	92.2	19.1	5.0	12.7	63.8	8.5	f	—	—	M8×50	8	UFC114G (82.4×63.7×2)
UFC114-065RH		113.5	63.8	92.2	19.1	7.0	12.7	63.8	8.5	g	63.5	59.5			
UFC152-000RH		151.6	—	130.3	21.3	4.8	14.3	102.0	8.5	f	—	—	M8×55	16	UFC152G (120.5×101.8×2)
UFC152-100RH		151.6	102.0	130.3	21.3	7.1	14.3	102.0	8.5	g	101.6	97.6			
UFC203-000RH		202.4	—	181.1	23.9	9.7	15.9	152.9	8.5	f	—	—	M8×60	20	UFC203G (171.2×152.6×2)
UFC203-150RH		202.4	152.9	181.1	23.9	12.7	15.9	152.9	8.5	g	152.4	146.4			
UFC253-000RH		253.2	—	231.9	24.6	9.7	17.2	203.7	8.5	f	—	—	M8×60	24	UFC253G (222.1×203.4×2)
UFC253-200RH		253.2	203.8	231.9	24.6	12.7	17.2	203.7	8.5	g	203.2	197.2			
UFC306-000RH		306.0	—	284.0	27.0	10.0	18.0	256.0	8.5	f	—	—	M8×65	32	UFC306G (273.0×258.0×2)
UFC306-250RH		306.0	256.0	284.0	27.0	13.0	18.0	256.0	8.5	g	254.0	248.0			